ROCKY MOUNTAIN RAIL PARK METROPOLITAN DISTRICT
INDUSTRIAL WASTEWATER DISCHARGE AUTHORIZATION

This form is structured for use under the Rocky Mountain Rail Park Metropolitan District Rules and Regulations.

Owner / Customer	
Facility	
Property Address	
Effective Date	
Expiration / Review Date	

AUTHORIZATION

Pursuant to the Rocky Mountain Rail Park Metropolitan District ("District") Rules and Regulations, including the provisions governing sanitary sewer service, industrial wastes, specially regulated wastes, pretreatment, Tap Certificates, inspection, and enforcement, the above Owner/Customer is authorized to discharge approved wastewater to the District sanitary sewer system only in accordance with this authorization, the applicable Tap Certificate, any Connector's or Service Agreement, and the District Rules and Regulations as now or hereafter lawfully amended.

This authorization does not permit any discharge prohibited by the District Rules and Regulations and does not waive any requirement of another governmental entity having jurisdiction.

A. BASIS AND SCOPE OF AUTHORIZATION

- The District sanitary sewer system is intended for sanitary sewage and approved industrial waste. Industrial waste may not be discharged without written permission from the District and payment of applicable fees.

- This authorization constitutes written District permission for the specific discharge described herein and is supplemental to, and not a substitute for, any required Tap Certificate, Connector's Agreement, Service Agreement, application for service, or payment of District fees and charges.

- The Owner/Customer shall use the District sewer system only for the approved premises, facility, processes, and wastewater described in this authorization. Waste generated off-site shall not be discharged through the authorized connection unless separately approved in writing by the District.

- Any increase or material change in wastewater flow, wastewater strength, industrial process, pretreatment system, use of the property, or service demand shall be reported to the District in advance and may require a modified Tap Certificate, additional information, additional fees, or revised conditions.

B. AUTHORIZED CONNECTION AND MONITORING POINT

Sewer Service Connection	
Monitoring Point	
Maximum Approved Flow	
Approved Process Wastewater	

☐ Standard discharge (BOD5/TSS ≤ 300 mg/L) ☐ High Strength Waste approved — surcharge applies per Section 6.10

The District may require the Owner/Customer, at its expense, to install and maintain an accessible control manhole or monitoring point, flow-measuring or sampling devices, emergency shutoff valves or gates, grease/oil/sand interceptors, or other pretreatment facilities. All such facilities shall be constructed and maintained in accordance with District-approved plans and specifications.

C. GENERAL DISCHARGE REQUIREMENTS AND PROHIBITIONS

No Person shall discharge or cause to be discharged wastewater that violates the District Rules and Regulations. Without limiting the Rules and Regulations, the following conditions apply to this authorization:

- No storm water, surface runoff, roof drainage, foundation drainage, subsurface drainage, or groundwater shall be discharged to the sanitary sewer system.
- No toxic or non-biodegradable waste, or waste that would cause treated effluent to fail applicable State of Colorado standards, may be discharged.
- No gasoline, benzene, naphtha, fuel oil, or other flammable or explosive liquid, solid, gas, oil, or grease may be discharged.
- No solid or viscous material capable of obstructing sewer flow or interfering with normal sewage or treatment works operation may be discharged.
- No concentrated waste from septic tanks or portable sanitary devices may be discharged.
- No hazardous chemicals may be discharged.
- No noxious or malodorous waste, water, gas, or substance capable of creating a public nuisance may be discharged.

D. DISTRICT DISCHARGE LIMITS

Unless the District establishes a more restrictive condition for the specific connection, wastewater discharged under this authorization shall comply with the following limits stated in Section 4.3 of the District Rules and Regulations:

Parameter / Condition	RMRPMD Limit	Basis / Sample
Temperature	Not greater than 104 °F	Overall effluent to wastewater treatment system
Animal or vegetable fat, oil or grease	100 ppm by weight maximum	Discharge
Ecoli (no/100 ml)	N/A	
pH	6.0 to 9.0	Discharge
5-day B.O.D.[1]	300 ppm maximum	Discharge
5-day C.O.D: B.O.D – Ratio	< 2:1	
Total Inorganic Nitrogen	50 mg/L	24-hour proportionate composite
Total Residual Chlorine	1 mg/L	24-hour proportionate composite
Suspended Solids[1]	300 ppm maximum	Discharge
Sulfates	0.05 mg/L	24-hour proportionate composite
Sulfide as (H2S)	1 mg/L	24-hour proportionate composite
Chloride	9 mg/L	24-hour proportionate composite
Methanol	2 mg/L	24-hour proportionate composite

[1] Wastewater exceeding 300 mg/L of BOD5 or TSS constitutes "high strength waste" under Section 4.3(b)(v) of the District Rules and Regulations. Discharge above this concentration is not permitted under this authorization unless the District has separately authorized acceptance of high strength waste in writing, subject to the conditions, pretreatment, and monitoring requirements the District may impose, and payment of the surcharge required under Section 6.10 of the District Rules and Regulations and the District's then-current schedule of fees, rates and charges.

Total Ammonia as N	50 mg/L	24-hour proportionate composite
Cadmium, TR	0.1 mg/L	24-hour proportionate composite
Cadmium, PD	0.1 mg/L	24-hour proportionate composite
Chromium +3, PD	0.2 mg/L	24-hour proportionate composite
Chromium, TR	0.2 mg/L	24-hour proportionate composite
Chromium +6, Dissolved	0.2 mg/L	24-hour proportionate composite
Copper, PD	0.3 mg/L	24-hour proportionate composite
Cyanides	2.0 mg/L	24-hour proportionate composite
Iron, Dissolved	5.0 mg/L	24-hour proportionate composite
Lead, TR	0.0005 mg/L	24-hour proportionate composite
Lead, PD	0.0005 mg/L	24-hour proportionate composite
Manganese, Dissolved	0.0378 mg/L	24-hour proportionate composite
Manganese, PD	0.0378 mg/L	24-hour proportionate composite
Molybdenum, TR	0.005 mg/L	24-hour proportionate composite
Mercury	0.00002 mg/L	24-hour proportionate composite
Nickel, TR	0.005 mg/L	24-hour proportionate composite
Nickel, PD	0.005 mg/L	24-hour proportionate composite
Selenium, PD	0.0005 mg/L	24-hour proportionate composite
Silver, PD	0.0005 mg/L	24-hour proportionate composite
Uranium, PD	0.0003 mg/L	24-hour proportionate composite
Phenol	3.0 mg/L	24-hour proportionate composite
Phosphorus	5 mg/L	24-hour proportionate composite
Aluminum, TR	0.005 mg/L	24-hour proportionate composite
Arsenic, TR	0.00006 mg/L	24-hour proportionate composite
Arsenic, PD	0.00006 mg/L	24-hour proportionate composite
Zinc, PD	0.6 mg/L	24-hour proportionate composite

- High Strength Waste. This authorization does not authorize discharge of high strength waste (wastewater exceeding 300 mg/L BOD5 or TSS, or such other concentration as the Board may establish) except as separately and expressly approved in writing by the District under Section 4.3(b)(v) of the District Rules and Regulations. If the Owner/Customer's discharge is expected to exceed, or does exceed, these concentrations, the Owner/Customer must apply for and obtain the District's written approval to discharge as high strength waste before doing so. Any such approval will be conditioned on compliance with applicable pretreatment, monitoring, and sampling requirements and payment of the High Strength Waste Surcharge under Section 6.10 of the District Rules and Regulations. Payment of the surcharge does not authorize discharge of any waste otherwise prohibited by the Rules and Regulations and does not excuse compliance with any other requirement therein.

E. PRETREATMENT AND OPERATION

- Where the District determines pretreatment is necessary, the Owner/Customer shall provide such pretreatment at its own expense. Pretreatment facilities shall be approved as required by the District and applicable State authorities and shall be continuously maintained in satisfactory and effective operation.

- Grease, oil, sand traps or interceptors, if required by the District, shall be installed, operated, cleaned, pumped, and maintained at the Owner/Customer's expense and shall remain readily accessible for inspection.
- The Owner/Customer shall not bypass, disable, tamper with, or operate around any required pretreatment, monitoring, flow-measurement, sampling, or emergency shutoff equipment except with prior written District approval or as necessary to protect life or property in an emergency, followed by prompt notice to the District.
- All solids, sludges, grease, oil, sand, or other materials removed by pretreatment shall be managed and disposed of so that they do not enter the District sewer system.

F. MONITORING, SAMPLING, AND RECORDS

The following facility-specific monitoring schedule may be required as a condition of this authorization. The District may revise the schedule based on discharge characteristics, compliance history, or operational needs.

Parameter	Location	Sample Type	Frequency	Limit / Report
Flow	Monitoring Point	Meter / Totalizer	Continuous / Monthly	Approved flow
pH	Monitoring Point	Grab / Continuous	Monthly	6.0 - 9.0
BOD5	Monitoring Point	Composite	Monthly	<= 300 mg/L
Suspended Solids	Monitoring Point	Composite	Monthly	<= 300 mg/L
[Other]	*[Monitoring Point]*	*[Type]*	*[Frequency]*	*[Limit / Report]*

- Sampling shall be representative of the authorized discharge and shall be performed at the approved monitoring point unless the District approves another location.
- The Owner/Customer shall retain monitoring, laboratory, cleaning, pumping, maintenance, and pretreatment records for at least THREE years or for any longer period required by applicable law or District direction.
- Upon request, the Owner/Customer shall promptly provide the District with monitoring results, laboratory reports, flow records, pretreatment records, waste-hauling records, and other information reasonably necessary to evaluate compliance.

G. NOTICE OF CHANGES, UPSETS, SPILLS, AND NONCOMPLIANCE

- The Owner/Customer shall promptly notify the District of any actual or threatened discharge that may violate this authorization or the District Rules and Regulations, cause contamination, pollution or nuisance, damage District facilities, interfere with sewer or treatment operations, or endanger public health or safety.
- The Owner/Customer shall take immediate reasonable action to stop or control the discharge, protect the District system, and prevent recurrence.
- For any material change in process, wastewater characteristics, flow, pretreatment, equipment, service, or property use, the Owner/Customer shall obtain District approval before implementing the change when required by the Rules and Regulations.
- If the Owner/Customer's wastewater characteristics change such that BOD5 or TSS concentrations are expected to exceed the limits in Section D, the Owner/Customer shall notify the District in advance and apply for high strength waste approval under Section 4.3(b)(v) and the applicable surcharge under Section 6.10 before discharging at the increased strength.

H. ACCESS AND INSPECTION

The Owner/Customer shall provide the District Manager, Inspector, Engineer, agents, officers, employees, representatives, and other authorized governmental representatives with access as permitted by the District Rules and Regulations for inspection, observation, measurement, sampling, testing, and review of facilities and records. Monitoring points, interceptors, meters, and related facilities shall remain safe and readily accessible.

I. OWNER/CUSTOMER RESPONSIBILITIES

- Maintain the entire Sewer Service Line as required by the District Rules and Regulations and promptly repair infiltration leaks, breaks, or other defects within 72 hours after notice.
- Pay all applicable Tap Fees, Service Charges, inspection costs, repair costs, penalties, and other amounts properly assessed by the District.
- Maintain all required pretreatment and pollution-control equipment in effective operating condition.
- Prevent unauthorized connections, unauthorized discharges, and tampering with District systems or monitoring equipment.
- Ensure employees, tenants, contractors, and operators whose activities may affect the discharge understand and comply with the conditions of this authorization.
- Comply with the District Rules and Regulations, the applicable Tap Certificate and agreements, and all applicable federal, state, and local requirements.

J. ENFORCEMENT AND SERVICE DISCONNECTION

Violation of this authorization, a Tap Certificate, or the District Rules and Regulations may result in enforcement by the District. Applicable remedies under the Rules and Regulations include correction or abatement of a public nuisance, assessment of costs, civil liability, termination of service, and disconnection of the Sewer Service Line.

- For a discharge or operation that violates the Rules and Regulations or causes or threatens contamination, pollution, or nuisance, the District may issue written notice requiring correction. The Rules and Regulations provide a 72-hour correction notice for the sewer-discharge enforcement circumstances described in Section 4.5(d).
- If the violation is not corrected, the District may take the enforcement actions authorized by its Rules and Regulations, including turning off water service or disconnecting the Sewer Service Line until adequate assurances of future compliance are provided.
- Where a discharge causes obstruction, damage, or impairment to District facilities, the Owner/Customer may be charged the District's costs to clean or repair the facilities, with collection remedies as provided by the Rules and Regulations.
- In an emergency, the District may terminate service without prior notice as authorized by the Rules and Regulations.

K. MODIFICATION, SUSPENSION, REVOCATION, AND TRANSFER

- This authorization may be modified, suspended, or revoked by the District as allowed by the District Rules and Regulations and any applicable Tap Certificate or agreement.
- Any approval of high strength waste discharge under Section D is independently subject to modification, suspension, or revocation by the District at any time, regardless of the status of this authorization as a whole.
- The authorization is limited to the identified property, connection, Owner/Customer, and approved use. No right to discharge at another property or through another connection is created.
- A change in ownership or operator does not excuse compliance. The new Owner/Customer shall provide updated contact and facility information and shall execute any District documents required to continue service.
- Nothing in this authorization prevents the District from imposing additional lawful conditions necessary to protect the District sewer system, treatment facilities, public health, safety, welfare, or receiving waters.

L. ACKNOWLEDGEMENT AND ACCEPTANCE

The undersigned acknowledges receipt of this authorization and agrees that use of the District sanitary sewer system is conditioned upon compliance with the District Rules and Regulations, the applicable Tap Certificate and agreements, and the conditions stated herein.

Owner / Customer

Authorized Representative

Title

Signature

Date

ROCKY MOUNTAIN RAIL PARK METROPOLITAN DISTRICT

Authorized By

Title

Signature / Date

District Determination — High Strength Waste

☐ Not applicable — discharge is not expected to exceed 300 mg/L BOD5 or TSS.

☐ Approved — District authorizes discharge of high strength waste up to the following limits, subject to the conditions below.

☐ Disapproved — District does not authorize discharge above the standard limits in this Section D. Owner/Customer shall not discharge wastewater exceeding 300 mg/L BOD5 or TSS under this authorization.

If Approved:
Approved BOD5 limit: _____ mg/L Approved TSS limit: _____ mg/L
Surcharge rate/basis (per District Schedule of Fees, Rates and Charges, Section 6.10): _____
Additional conditions (pretreatment, monitoring, sampling, reporting): _____
Approval effective from: _____ to (review/expiration date): _____

This determination is discretionary and may be conditioned, limited, suspended, or revoked by the District at any time in accordance with Section 6.10(a) of the District Rules and Regulations. Approval of high strength waste discharge does not authorize any waste otherwise prohibited under Section 4.3 and does not excuse compliance with any other requirement of the Rules and Regulations.

Reviewed and Determined By (District):
Name/Title: _____
Signature: _____
Date: _____